



Manifold Type FBH-VL-RL Stainless Steel

shipment:

**a fully furnished manifold centre for 2-12 heating circuits
light and durable, with stainless steel body made according to EN
10088-2, Material: 1.4301 (X5CrNi18-10):**



- 2 x air vents 1/2", nickel-plated
- 2 x filling/draining valves 1/2", nickel-plated, plastic black
- 2 x end caps 1", nickel-plated
- For each circuit: connector nipples 3/4" (male connection), Euro cone, DIN V 3838, nickel-plated
- **Distance between the circuits: 50 mm**
- 2 x connections to the rest of the system with 1" union nuts (female connection), nickel-plated
- Outflow: manifold with adjustable flow meters Type RL-V-0-5 l/min to regulate the water flow
- Return: manifold with Thermostatic valves for each circuit, hand wheels blue
- 2 x mounting brackets, completely with screws and plugs in the package (brackets are not mounted on manifolds like drawing), **Type 10/30/200**
- Package

Ball valves for manifolds

Ball valve 1" female x 1" male, flat gasket:

<u>Circuits</u>	<u>Size (Length)</u>
2	210mm
3	260mm
4	310mm
5	360mm
6	410mm
7	460mm
8	510mm
9	560mm
10	610mm
11	660mm
12	710mm